

REPORT DOCUMENTATION PAGE					Form Approved OMB No. 0704-0188	
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>						
1. REPORT DATE (DD-MM-YYYY) 10-01-2008		2. REPORT TYPE Performance/Technical Report (Bi-annual)		3. DATES COVERED (From - To) Jun 2007 - Dec 2007		
4. TITLE AND SUBTITLE Wireless Cooperative Networks: Self-Configuration and Optimization FY07 Year End Report				5a. CONTRACT NUMBER		
				5b. GRANT NUMBER N00014-07-1-0868		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Liuqing Yang				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Florida Office of Engineering Research 343 Weil Hall, PO Box 116550 Gainesville, FL 32611				8. PERFORMING ORGANIZATION REPORT NUMBER #1		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Office of Naval Research 875 North Randolph Street Arlington, VA 22203-1995				10. SPONSOR/MONITOR'S ACRONYM(S) ONR		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for Public Release; distribution is Unlimited.						
13. SUPPLEMENTARY NOTES						
14. ABSTRACT <p>In wireless sensor networks, relay transmissions can enable cooperative diversity by forming virtual antenna arrays. The optimum resource allocation in such systems is critical to enhance their error rate performance and energy efficiency. Existing work often focus on the optimization of the energy allocation among the source and relay nodes. This is not only undesirable from the relays' point of view especially when they are required to transmit at high power levels, but also impossible at times since the sensor nodes are each limited by their individual battery capacity. On the other hand, the source is very likely to have multiple candidates to choose from. In a mobile sensor network, the relay nodes can also move to desirable locations to better assist the communication from the source node to the destination node. In order to exploit the freedom in terms of relay location, we treat the resource allocation in relay networks as a two-dimensional (energy and location) optimization problem and establish some very interesting results. To facilitate the implementation of such an optimum strategy, we also investigated precise localization techniques for wireless sensor networks.</p>						
15. SUBJECT TERMS wireless sensor networks, wireless cooperative networks, resource optimization, ultra-wideband, localization, ranging						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON	
a. REPORT	b. ABSTRACT	c. THIS PAGE			Liuqing Yang	
U	U	U	UU	4	19b. TELEPHONE NUMBER (Include area code) (352)392-9469	

FY07 Year End Report

WIRELESS COOPERATIVE NETWORKS: SELF-CONFIGURATION AND OPTIMIZATION

Liuqing Yang

(Technical Point of Contact)

Dept. of Electrical and Computer Engineering

P.O. Box 116130

University of Florida

Gainesville, FL 32611

Tel: (352) 392-9469

Fax: (352) 392-0044

Email: lqyang@ece.ufl.edu

Ms. Roslyn S. Oleson

(Administrative Point of Contact)

Office of Engineering Research

College of Engineering

P.O. Box 116550

University of Florida

Gainesville, FL 32611-6550

Tel: (352) 392-9447 ext. 7

Fax: (352) 846-1471

Email: roleson@ufl.edu

20080118053

A Abstract

In wireless sensor networks, relay transmissions can enable cooperative diversity by forming virtual antenna arrays. The optimum resource allocation in such systems is critical to enhance their error rate performance and energy efficiency. Existing work often focus on the optimization of the energy allocation among the source and relay nodes. This is not only undesirable from the relays' point of view especially when they are required to transmit at high power levels, but also impossible at times since the sensor nodes are each limited by their individual battery capacity. On the other hand, the source is very likely to have multiple candidates to choose from. In a mobile sensor network, the relay nodes can also move to desirable locations to better assist the communication from the source node to the destination node. In order to exploit the freedom in terms of relay location, we treat the resource allocation in relay networks as a two-dimensional (energy and location) optimization problem and establish some very interesting results. To facilitate the implementation of such an optimum strategy, we also investigated precise localization techniques for wireless sensor networks.

B Technical Results

We consider two prevalent relay protocols for wireless sensor networks: decode-and-forward and amplify-and-forward. To alleviate the channel estimation load at the receiver side, we consider differential modulation and demodulation for both protocols. We derive a tight upper bound of the error performance for the decode-and-forward case and a close approximation of the error performance for the amplify-and-forward case. Both are simple closed-form expressions accounting for arbitrary number of relays and possible existence of a direct wireless link from the source node to the destination node.

Based on these closed-form expressions, we then establish the optimum energy allocation strategy at the source and relay nodes given any source-relay-destination distances, and the optimum relay location selection for any energy distribution at the source and relay nodes. On top of these uncoupled optimizations, our error performance bound and approximation also allows for numerical search (as opposed to extensive simulations) of the global optimum operation condition which maximally reduces the total energy consumption or extends the communication range.

Our extensive analytical and simulated comparisons confirm that the optimized systems provide considerable improvement over un-optimized ones. We also show that the relay location optimization, which has been long neglected in related studies, may be more critical than the energy optimization.

tion. In addition, our joint optimization often results in considerably reduced power consumption at the relay nodes. This is favorable to wireless sensor networks where each node may have its own sensing data to transmit, since they can maximally conserve energy when helping others as relays.

To enable the implementation of such an optimum strategy in wireless sensor networks, the sensor nodes need to know their precise (absolute or relative) locations. In the past, the Global Positioning System (GPS) has been the major method for wireless localization and navigation. However, its application is constrained since the GPS signal is not available in indoor, metropolitan and heavy-foliage scenarios which, more often than not, are where the sensor networks are deployed. Therefore, we need to exploit alternative terrestrial wireless signals for positioning and navigation. In our work, we consider both the ultra-wideband (UWB) signals that are intentionally set up, and the wireless local area network (WLAN) IEEE 802.11a/g signals that are widely available and are known as the “signal-of-opportunity.” For both signals, we investigate the time-difference-of-arrival (TDoA) based ranging and localization.

The Cramer-Rao Bound (CRB) analysis shows that UWB signals can provide high resolution timing and positioning, thanks to its huge bandwidth. However, in practical implementation, the CRB can not be achieved because the perfect channel information may not be available at the receiver. To this end, we investigate how to exploit the huge bandwidth for high resolution ranging in practical scenarios. We compare the coherent and noncoherent combining of the multi-band signals for ranging. The comparisons show that a high timing resolution can be achieved by combining the channel information from multiple sub-bands in a coherent manner. However, when the channel is independent across sub-bands, the multi-band signals can only be combined in a noncoherent manner to improve the mis-timing performance. In particular, the slope of the probability of mis-timing curve becomes steeper as the number of sub-bands increases. This is reminiscent of the concept of diversity known in communications.

We also propose a simple model-based time-of-arrival (ToA) estimation approach. In this approach, the channel impulse response (CIR) is recovered with a simple equally-spaced model. Then, the delay of channel path is estimated by minimizing the energy leakage from the first path. Compared with the widely adopted space alternating generalized expectation maximization (SAGE) algorithm, our model-based approach has the advantage of lower complexity while providing similar or better ranging performance. Based on this ToA estimator, we realize the TDoA-based and TDoA-Doppler hybrid localization algorithms. Simulations are also carried out to corroborate our theoretical analysis.

C References

- [1] W. Cho and L. Yang, "Optimum Resource Allocation for Relay Networks with Differential Modulation," *IEEE Transactions on Communications*, 2008 (to appear).
- [2] H. Xu and L. Yang, "Performance Analysis of The Energy Detection Based ToA Estimator for MB-OFDM UWB," in *Proceedings of URSI (Union Radio Scientifique Internationale) General Assembly*, Chicago, IL, August 07-16, 2008 (invited).
- [3] W. Cho and L. Yang, "Performance Analysis of Cooperative Networks with Differential Unitary Space Time Coding," in *Proceedings of International Conference on Acoustics, Speech and Signal Processing*, Las Vegas, NV, March 30-April 4, 2008 (to appear).
- [4] H. Xu and L. Yang, "Ultra-Wideband Technology: Yesterday, Today, and Tomorrow," in *Proceedings of IEEE Radio and Wireless Symposium*, Orlando, FL, January 22-24, 2008 (invited).
- [5] W. Cho and L. Yang, "Resource Allocation for Amplify-and-Forward Relay Networks with Differential Modulation," in *Proceedings of IEEE Global Telecommunications Conference*, Washington, D.C., November 26-30, 2007.
- [6] W. Cho, R. Cao and L. Yang, "Optimum Energy Allocation in Cooperative Networks: A Comparative Study," in *Proceedings of IEEE Military Communication Conference*, Orlando, FL, October 29-31, 2007.
- [7] H. Xu and L. Yang, "Opportunistic Indoor Localization and Navigation Using Wireless LAN (802.11a/g) Signals," in *Proceedings of ION GNSS 2007*, Fort Worth, TX, September 25-28, 2007.
- [8] L. Yang, H. Xu and Y. T. Jade Morton, "Positioning and Navigation with Ultra-Wideband Signals," in *Proceedings of ION GNSS 2007*, Fort Worth, TX, September 25-28, 2007.
- [9] F. Qu, D. Duan, L. Yang, and A. Swami "Signaling With Imperfect Channel State Information: A Battery Power Efficiency Comparison," *IEEE Transactions on Signal Processing*, September 2007 (submitted).
- [10] W. Cho, R. Cao and L. Yang, "Optimum Resource Allocation for Amplify-and-Forward Relay Networks with Differential Modulation," *IEEE Transactions on Signal Processing*, June 2007 (submitted).